

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>5</sup> : B22D 39/00, H01M 2/28 B22D 25/04	A1	(11) International Publication Number: WO 91/05625 (43) International Publication Date: 2 May 1991 (02.05.91)
--	----	--

(21) International Application Number: PCT/GB90/01593

(22) International Filing Date: 16 October 1990 (16.10.90)

(30) Priority data:  
8923690.5 20 October 1989 (20.10.89) GB

(71) Applicant (for all designated States except US): DRG (UK) LIMITED [GB/GB]; 1 Redcliffe Street, Bristol, Avon BS99 7QY (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): HOPWOOD, Robert, Timothy [GB/GB]; 34 Alma Road, Hatherley, Cheltenham, Gloucestershire GL51 5LZ (GB).


(74) Agents: DUNLOP, Brian, Kenneth, Charles et al.; Wynne-Jones, Laine &amp; James, 22 Rodney Road, Cheltenham, Gloucestershire GL50 1JJ (GB).

(81) Designated States: AT (European patent), AU, BE (European patent), CA, CH (European patent), DE (European patent), DK (European patent), ES (European patent), FR (European patent), GB (European patent), GR (European patent), IT (European patent), JP, LU (European patent), NL (European patent), SE (European patent), US.

## Published

*With international search report.**Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.*

(54) Title: CASTING APPARATUS FOR CONNECTING A BATTERY PLATE TO A METAL STRAP



## (57) Abstract

Moulding apparatus (10) includes a lead pot (11), a pump unit (12) and a mould block (13), having feed duct (14). The feed duct (14) communicates with the pump unit (12) by means of a supply passage (17), which is also connected to an overflow outlet (18), which can be closed by a dump valve (19). In normal operation the level of the lead in the feed duct is kept to a datum level (23) defined by the overflow. During 'pouring' however the dump valve (19) is closed.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	ES	Spain	MG	Madagascar
AU	Australia	FI	Finland	ML	Mali
BB	Barbados	FR	France	MR	Mauritania
BE	Belgium	GA	Gabon	MW	Malawi
BF	Burkina Faso	GB	United Kingdom	NL	Netherlands
BG	Bulgaria	GR	Greece	NO	Norway
BJ	Benin	HU	Hungary	PL	Poland
BR	Brazil	IT	Italy	RO	Romania
CA	Canada	JP	Japan	SD	Sudan
CF	Central African Republic	KP	Democratic People's Republic of Korea	SE	Sweden
CG	Congo	KR	Republic of Korea	SN	Senegal
CH	Switzerland	LI	Liechtenstein	SU	Soviet Union
CI	Côte d'Ivoire	LK	Sri Lanka	TD	Chad
CM	Cameroon	LU	Luxembourg	TG	Togo
DE	Germany	MC	Monaco	US	United States of America
DK	Denmark				

CASTING APPARATUS FOR CONNECTING A BATTERY  
PLATE TO A METAL STRAP

This invention relates to casting apparatus of the type for connecting a battery plate to a metal strap or post.

Such apparatus was described in our British Patent No. 2,023,471B. In this arrangement a pump 13 delivers a metered shot of lead through an inlet valve 203 into a feed duct 52 causing lead to overflow into mould cavities 51. A dump valve 82 is then opened and the lead in the feed duct 52 falls back to a datum or constant head level defined by the level of the dump valve. Whilst this was a considerable improvement over existing casting arrangements certain problems have been experienced. First the inlet valve has a tendency to become clagged so that it does not seat properly. This results in the feed duct draining down into the lead pot and as a result the next "shot" of lead delivered by the pump results in insufficient filling of the cavities. Further the shockwave resulting from the delivery of the metered shot of lead causes ripples in the feed duct and hence incomplete filling of the cavities.

The present invention consists in apparatus for connecting a battery plate to a metal strap or post, including a mould having at least one strap or post cavity and a molten-metal feed duct adjacent thereto, a weir between the feed duct and the cavity, means for delivering molten-metal to one end of the feed duct

- 2 -

including a pump for substantially continuous operation and a dump valve for allowing metal to flow out of the duct to a predetermined datum level when open and for causing metal to flow through the weirs into the cavity, when closed.

5 By running the pump substantially continuously or completely continuously the shockwaves can be removed. In this constant running arrangement the overflowing of the lead from the feed duct into the cavities can be achieved in a number of ways. First the pump can be run at a  
10 single speed and overflow is achieved simply by closing the dump valve. This leads to a rather high circulation of lead and hence oxide formation. Secondly the pump may be run at at least two speeds; a first low speed which is designed simply to prevent the feed duct leaking down into  
15 the pot and a second high speed which will deliver an appropriate amount of lead into the feed duct for the cavities to be filled. By timing the period of the second high speed and the operation of the dump valve the lead could be metered quite precisely. Thirdly the  
20 apparatus may include an inlet valve between the pump and the feed duct. In this case if the inlet valve becomes clagged then the pump will prevent any leakage from the feed duct into the pot, whilst the open dump valve will prevent the feed duct overflowing. Fourthly,  
25 and indeed preferably the pump may be switched off for a very short period of time after the lead has flowed into the cavities, in order to increase the effective lead acting on the lead in the duct and hence the rate at which the predetermined datum level is achieved.

30 In a preferred embodiment the pump is an impeller pump and means are provided for closing the dump valve only when the cavities are to be filled. The means for

- 3 -

closing the dump valve may operate in response or in timed relationship with the opening and closing of the inlet valve. Alternatively in the situation where there is no inlet valve the means for closing the dump valve  
5 may operate in relation to the pump speed or some other cyclic element in the casting apparatus.

Although the invention has been defined above it is to be understood it includes any inventive combination of the features set out above or in the following  
10 description.

The invention may be performed in various ways and specific embodiments will now be described, by way of example, with reference to the accompanying drawings, in which:

15 Figure 1 is a diagrammatic side view of a casting apparatus; and

Figure 2 is a sectional view through the mould block of Figure 1.

The apparatus generally indicated at 10 comprises  
20 a lead pot 11, a pump unit 12 and a mould block 13.

The mould block 13 is essentially identical to that described in our previous Application but briefly it comprises a feed duct 14 separated from mould cavities 15 by weirs 16. The feed duct communicates with the pump  
25 unit 12 by means of a supply passage 17, which is also connected to an overflow outlet 18, which can be closed

- 4 -

by a dump valve 19.

The pump unit includes an impeller pump 20 and an inlet valve 21. The impeller pump 20 draws lead in from the lead pot 11 through an inlet 22 and, when the inlet valve 21 is open, feeds lead up into the supply passage 17 and hence into the feed duct 14.

In normal operation the level of lead in the feed duct 14 is kept to a datum level 23 defined by the overflow 18. When lead is to be poured into the mould cavities 15, the dump valve 19 closes the overflow 18 and the inlet 21 is opened allowing a sustained flow of lead into the feed duct 14 so that the lead overflows the weirs 16. The dump valve 19 is then opened and the inlet valve 21 closed (and the pump may be momentarily switched off) so that the lead in the feed duct falls back below the height of the weir 16 once sufficient lead has been poured into the cavities 15.

If, however, the inlet valve 21 becomes clagged so that it no longer seats properly any downwardly leakage from the supply passage is prevented by the flow of lead through the resultant gap up into the passage 17. If the rate of flow is such that excessive lead is received in the feed duct 14 then this will be regulated by the open overflow 18 which maintains the datum level. This method of operation saves a considerable downtime in the apparatus, because currently pumps are having to be stripped out once a week.

- 5 -

As has been mentioned above the alternative operations can be achieved in an arrangement omitting the inlet valve 21. Both valves are operated by hydraulic rams 24, 25 against springs 26, 27. The dump valve is preferably arranged to fail open.

In the drawings the dump valve is shown as a flap pivoted about an axis extending generally parallel to the direction of flow through the valve. Alternatively it may be pivoted about a transverse axis, so it closes against the flow rather than 'slicing' across it. This means it is less likely to become jammed by any clag build up. A further possibility is shown in Figure 3 in this case the dump valve 19 comprises a needle valve element 30 which locates in an 'open well' outlet 31 at the head of supply passage 17. The advantage of this arrangement is that it reduces the surface area of the lead which is exposed to the air and hence oxidisation and clagging.

- 6 -

CLAIMS

1. Apparatus for connecting a battery plate to a metal strap or post, including a mould having at least one strap or post cavity and a molten-metal feed duct adjacent thereto, a weir between the feed duct and the cavity, means  
5 for delivering molten-metal to one end of the feed duct including a pump for substantially continuous operation and a dump valve for allowing metal to flow out of the duct to a predetermined datum level when open and for causing metal to flow over the weirs into the cavity,  
10 when closed.
2. Apparatus as claimed in Claim 1, wherein there is an inlet valve between the pump and the feed duct.
3. Apparatus as claimed in Claim 1 or Claim 2, wherein the pump is an impeller pump.
- 15 4. Apparatus as claimed in any one of the preceding Claims, further including means for closing the dump valve only when the cavities are to be filled.
5. Apparatus as claimed in Claim 4, as dependent on Claim 2, wherein the means for closing the dump valve  
20 operates in response or in timed relationship with the opening of the inlet valve.
6. Apparatus as claimed in Claim 1, including means for driving the pump at more than one speed.
7. Apparatus as claimed in Claim 6, further including  
25 means for closing the dump valve when the pump is accelerated.



1/2




Fig. 1.




Fig. 2.

2/2




Fig.3.

I. CLASSIFICATION OF SUBJECT MATTER (if several classification symbols apply, indicate all)<sup>6</sup>

According to International Patent Classification (IPC) or to both National Classification and IPC

Int.Cl. 5 B22D39/00 ; H01M2/28 ; B22D25/04

## II. FIELDS SEARCHED

Minimum Documentation Searched<sup>7</sup>

Classification System	Classification Symbols
Int.Cl. 5	B22D ; H01M

Documentation Searched other than Minimum Documentation  
to the extent that such Documents are Included in the Fields Searched<sup>8</sup>III. DOCUMENTS CONSIDERED TO BE RELEVANT<sup>9</sup>

Category <sup>o</sup>	Citation of Document, <sup>11</sup> with indication, where appropriate, of the relevant passages <sup>12</sup>	Relevant to Claim No. <sup>13</sup>
A	EP,A,221331 (INTERATOM) 13 May 1987 see abstract; claims ; figures ----	1
A	US,A,4053012 (FARMER) 11 October 1977 see abstract; claims ; figures ----	1
A	US,A,4180120 (EBERLE) 25 December 1979 see abstract; claims ----	1

<sup>o</sup> Special categories of cited documents : <sup>10</sup>

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

## IV. CERTIFICATION

Date of the Actual Completion of the International Search

15 FEBRUARY 1991

Date of Mailing of this International Search Report


22 MAR 1991

International Searching Authority

EUROPEAN PATENT OFFICE

Signature of Authorized Officer

Mme N. KUIPER



ANNEX TO THE INTERNATIONAL SEARCH REPORT  
ON INTERNATIONAL PATENT APPLICATION NO.

GB 9001593

SA 41118

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information. 04/03/

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP-A-221331	13-05-87	None	
US-A-4053012	11-10-77	None	
US-A-4180120	25-12-79	US-A- 3861575	21-01-75
		CA-A- 1129950	17-08-82
		JP-A- 55010392	24-01-80
		US-A- 4266597	12-05-81
		US-A- 3954216	04-05-76
		US-A- 3942704	09-03-76